

WATTYL ACID CAT CLEAR PART A

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet
Issue Date: 14-Sep-2013
X9317SP

CHEMWATCH 5072-63
Version No:8.1.1.1
Page 1 of 13

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

WATTYL ACID CAT CLEAR PART A

SYNONYMS

"All Gloss Levels", "Manufacturers Gloss Levels"

PROPER SHIPPING NAME

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

PRODUCT USE

Used according to manufacturer's directions.

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

SUPPLIER

Company: Valspar Australia Pty Ltd Pty Limited

Address:

Level 4, 2 Burbank Place

Baulkham Hills

NSW, 2153

Australia

Telephone: +61 2 8867 3333

Emergency Tel: +61 1800 039 008

Emergency Tel: +61 3 9573 3112

Fax: +61 2 8867 3344

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

RISK

Risk Codes

R11

R40(3)

R41

R43

R20/21/22?

R33?

R37/38?

R42?

R65?

R66?

R67?

Risk Phrases

- Highly flammable.
- Limited evidence of a carcinogenic effect.
- Risk of serious damage to eyes.
- May cause SENSITISATION by skin contact.
- Inhalation, skin contact and/or ingestion may produce health damage*.
- Cumulative effects may result following exposure*.
- May produce discomfort of the respiratory system and skin*.
- Possible respiratory sensitiser*.
- HARMFUL- May cause lung damage if swallowed.
- Repeated exposure potentially causes skin dryness and cracking*.
- Vapours potentially cause drowsiness and dizziness*.

SAFETY

Safety Codes

S16

S23

S24

S25

S36

S37

S39

Safety Phrases

- Keep away from sources of ignition. No smoking.
- Do not breathe gas/fumes/vapour/spray.
- Avoid contact with skin.
- Avoid contact with eyes.
- Wear suitable protective clothing.
- Wear suitable gloves.
- Wear eye/face protection.

continued...

WATTYL ACID CAT CLEAR PART A

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet

Issue Date: 14-Sep-2013

X9317SP

CHEMWATCH 5072-63

Version No:8.1.1.1

Page 2 of 13

Section 2 - HAZARDS IDENTIFICATION

S51	• Use only in well ventilated areas.
S09	• Keep container in a well ventilated place.
S29	• Do not empty into drains.
S401	• To clean the floor and all objects contaminated by this material, use water and detergent.
S07	• Keep container tightly closed.
S13	• Keep away from food, drink and animal feeding stuffs.
S26	• In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
S46	• If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
S60	• This material and its container must be disposed of as hazardous waste.
S63	• In case of accident by inhalation: remove casualty to fresh air and keep at rest.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
alkyd resin solution	Various	30-60
urea/ formaldehyde resin solution, butylated	68002-19-7	5-15
n- propanol	71-23-8	1-9
n- butyl acetate	123-86-4	1-9
nitrocellulose with >25% alcohol, <12.6% nitrogen	Not avail.	1-9
methyl ethyl ketone	78-93-3	1-9
methyl isobutyl ketone	108-10-1	1-5
n- butanol	71-36-3	1-2
silica amorphous	7631-86-9	0-5
additives		1-9

NOTE: Manufacturer has supplied full ingredient information to allow CHEMWATCH assessment.

Section 4 - FIRST AID MEASURES

SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.

EYE

- If this product comes in contact with the eyes:
 - Immediately hold eyelids apart and flush the eye continuously with running water.
 - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
 - Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.
 - Transport to hospital or doctor without delay.

SKIN

- If skin contact occurs:
 - Immediately remove all contaminated clothing, including footwear.
 - Flush skin and hair with running water (and soap if available).
 - Seek medical attention in event of irritation.

INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket

continued...

WATTYL ACID CAT CLEAR PART A

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet
Issue Date: 14-Sep-2013
X9317SP

CHEMWATCH 5072-63

Version No:8.1.1.1

Page 3 of 13

Section 4 - FIRST AID MEASURES

mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.

Treat symptomatically.

for simple esters:

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
 - Watch for signs of respiratory insufficiency and assist ventilation as necessary.
 - Administer oxygen by non-rebreather mask at 10 to 15 l/min.
 - Monitor and treat, where necessary, for pulmonary oedema .
- To treat poisoning by the higher aliphatic alcohols (up to C7):
- Gastric lavage with copious amounts of water.
 - It may be beneficial to instill 60 ml of mineral oil into the stomach.
 - Oxygen and artificial respiration as needed.
 - Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- Water spray or fog.
- Alcohol stable foam.
- Dry chemical powder.
- Carbon dioxide.

Do not use a water jet to fight fire.

FIRE FIGHTING

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves in the event of a fire.
- Prevent, by any means available, spillage from entering drains or water course.

FIRE/EXPLOSION HAZARD

- Liquid and vapour are highly flammable.
 - Severe fire hazard when exposed to heat, flame and/or oxidisers.
 - Vapour may travel a considerable distance to source of ignition.
 - Heating may cause expansion or decomposition leading to violent rupture of containers.
- Combustion products include: carbon dioxide (CO₂), formaldehyde, other pyrolysis products typical of burning organic material.
- Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

FIRE INCOMPATIBILITY

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

•3YE

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

MAJOR SPILLS

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.

continued...

WATTYL ACID CAT CLEAR PART A

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet
Issue Date: 14-Sep-2013
X9317SP

CHEMWATCH 5072-63
Version No:8.1.1.1
Page 4 of 13

Section 6 - ACCIDENTAL RELEASE MEASURES

- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- DO NOT allow clothing wet with material to stay in contact with skin.
- Electrostatic discharge may be generated during pumping - this may result in fire.
- Ensure electrical continuity by bonding and grounding (earthing) all equipment.
- Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec).
- Avoid splash filling.
- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.

STORAGE INCOMPATIBILITY

Alcohols

- are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.
- reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen
- react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium
- should not be heated above 49 deg. C. when in contact with aluminium equipment.
- Esters react with acids to liberate heat along with alcohols and acids.
- Strong oxidising acids may cause a vigorous reaction with esters that is sufficiently exothermic to ignite the reaction products.
- Heat is also generated by the interaction of esters with caustic solutions.
- Flammable hydrogen is generated by mixing esters with alkali metals and hydrides.

STORAGE REQUIREMENTS

- Store in original containers in approved flame-proof area.
- No smoking, naked lights, heat or ignition sources.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
_____	_____	_____	_____	_____	_____	_____	_____	_____	_____

continued...

WATTYL ACID CAT CLEAR PART A

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet
Issue Date: 14-Sep-2013
X9317SP

CHEMWATCH 5072-63
Version No:8.1.1.1
Page 5 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Source	Material	TWA ppm	TWA mg/m ³	STEL ppm	STEL mg/m ³	Peak ppm	Peak mg/m ³	TWA F/CC	Notes
Australia Exposure Standards	n- propanol (Propyl alcohol)	200		250	614				
Australia Exposure Standards	n- butyl acetate (n- Butyl acetate)	150		200	950				
Australia Exposure Standards	methyl ethyl ketone (Methyl ethyl ketone (MEK))	150		300	890				
Australia Exposure Standards	methyl isobutyl ketone (Methyl isobutyl ketone)	50		75	307				
Australia Exposure Standards	n- butanol (n- Butyl alcohol)	50							

The following materials had no OELs on our records
• urea/ formaldehyde resin solution, butylated:

CAS:68002- 19- 7

MATERIAL DATA

METHYL ETHYL KETONE:
METHYL ISOBUTYL KETONE:
N-BUTANOL:
N-BUTYL ACETATE:
N-PROPANOL:

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.
Odour Safety Factor (OSF) is determined to fall into either Class A or B.
The Odour Safety Factor (OSF) is defined as:
OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm
Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

N-BUTANOL:
UREA/ FORMALDEHYDE RESIN SOLUTION, BUTYLATED:

For n-butanol:
Odour Threshold Value: 0.12-3.4 ppm (detection), 1.0-3.5 ppm (recognition)

NOTE: Detector tubes for n-butanol, measuring in excess of 5 ppm are commercially available.

Exposure at or below the TLV-TWA is thought to provide protection against hearing loss due to vestibular and auditory nerve damage in younger workers and to protect against the significant risk of headache and irritation.

25 ppm may produce mild irritation of the respiratory tract 50 ppm may produce headache and vertigo.

Higher concentrations may produce marked irritation, sore throat, coughing, nausea, shortness of breath, pulmonary injury and central nervous system depression characterised by headache, dizziness, dullness and drowsiness.

continued...

WATTYL ACID CAT CLEAR PART A

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet

Issue Date: 14-Sep-2013

X9317SP

CHEMWATCH 5072-63

Version No:8.1.1.1

Page 6 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

ALKYD RESIN SOLUTION:

UREA/ FORMALDEHYDE RESIN SOLUTION, BUTYLATED:

No exposure limits set by NOHSC or ACGIH.

WATTYL ACID CAT CLEAR PART A:

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

UREA/ FORMALDEHYDE RESIN SOLUTION, BUTYLATED:

for formaldehyde:

Odour Threshold Value for formaldehyde: 0.98 ppm (recognition)

NOTE: Detector tubes for formaldehyde, measuring in excess of 0.2 ppm are available commercially.

Formaldehyde vapour exposure:

Primary irritation is dependent on duration of exposure and individual susceptibility.

The following are typical symptoms encountered at various exposure levels.

0.1 ppm - Lower level of mucous eye, nose and throat irritation

0.8 ppm - Typical threshold of perception

1-2 ppm - Typical threshold of irritation

2-3 ppm - Irritation of eyes, nose and throat

4-5 ppm - Increased irritation, tearing, headache, pungent odour

10-20 ppm - Profuse tearing, severe burning, coughing

50 ppm - Serious bronchial and alveolar damage

100 ppm - Formaldehyde induced chemical pneumonia and death

Despite the intent of the TLV Ceiling recommendation it is believed that 0.3 ppm will not protect that portion of the workforce (up to 20%) reported to be responsive to low ambient concentrations. Because of the dose-related carcinogenic activity for rat and mouse inhalation of formaldehyde, the report of macromolecular adducts in the upper and lower respiratory tracts of nonhuman primates following inhalation of formaldehyde, the human case reports of upper respiratory tract malignant melanoma associated with.

N-PROPANOL:

For n-propanol:

IDLH Level: 800 ppm

Odour threshold level: 0.13-30 ppm.

Because n-propanol has the same biological effects as isopropanol but is less toxic, the TLV-TWA is intermediate between the limits for isopropyl alcohol and the butanols.

Odour Safety Factor(OSF)

OSF=77 (n-PROPANOL).

N-BUTYL ACETATE:

For n-butyl acetate

Odour Threshold Value: 0.0063 ppm (detection), 0.038-12 ppm (recognition)

Exposure at or below the recommended TLV-TWA is thought to prevent significant irritation of the eyes and respiratory passages as well as narcotic effects. In light of the lack of substantive evidence regarding teratogenicity and a review of acute oral data a STEL is considered inappropriate.

Odour Safety Factor(OSF)

OSF=3.8E2 (n-BUTYL ACETATE).

NITROCELLULOSE WITH >25% ALCOHOL, <12.6% NITROGEN:

None assigned. Refer to individual constituents.

nitrocellulose:

None assigned.

methylated spirits, as ethanol:

TLV TWA: 1000 ppm, 1880 mg/m3

ES TWA: 1000 ppm, 1900 mg/m3

METHYL ETHYL KETONE:

For methyl ethyl ketone:

Odour Threshold Value: Variously reported as 2 ppm and 4.8 ppm

Odour threshold: 2 ppm (detection); 5 ppm (recognition) 25 ppm (easy recognition); 300 ppm IRRITATING

Exposures at or below the recommended TLV-TWA are thought to prevent injurious systemic effects and to minimise objections to odour and irritation. Where synergism or potentiation may occur stringent control of the primary toxin (e.g. n-hexane or methyl butyl ketone) is desirable and additional consideration should be given to lowering MEK exposures.

Odour Safety Factor(OSF)

OSF=28 (METHYL ETHYL KETONE).

continued...

WATTYL ACID CAT CLEAR PART A

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet

Issue Date: 14-Sep-2013

X9317SP

CHEMWATCH 5072-63

Version No:8.1.1.1

Page 7 of 13

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

METHYL ISOBUTYL KETONE:

for methyl isobutyl ketone (MIBK):

Unfatigued, odour recognition threshold (100% test panel) is 0.3 - 0.5 ppm.

Distinct odour at 15 ppm.

Odour is objectionable and vapours are irritating to eyes at 200 ppm.

NOTE: Detector tubes for methyl isobutyl ketone, measuring in excess of 50 ppm, are commercially available.

SILICA AMORPHOUS:

The concentration of dust, for application of respirable dust limits, is to be determined from the fraction that penetrates a separator whose size collection efficiency is described by a cumulative log-normal function with a median aerodynamic diameter of 4.0 µm (+-) 0.3 µm and with a geometric standard deviation of 1.5 µm (+-) 0.1 µm, i.e. generally less than 5 µm.

For amorphous crystalline silica (precipitated silicic acid):

Amorphous crystalline silica shows little potential for producing adverse effects on the lung and exposure standards should reflect a particulate of low intrinsic toxicity. Mixtures of amorphous silicas/ diatomaceous earth and crystalline silica should be monitored as if they comprise only the crystalline forms.

The dusts from precipitated silica and silica gel produce little adverse effect on pulmonary functions and are not known to produce significant disease or toxic effect.

IARC has classified silica, amorphous as Group 3: NOT classifiable as to its carcinogenicity to humans.

PERSONAL PROTECTION

RESPIRATOR

• Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

- Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber.

NOTE:

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.

ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

continued...

WATTYL ACID CAT CLEAR PART A

Chemwatch Material Safety Data Sheet
Issue Date: 14-Sep-2013
X9317SP

Hazard Alert Code: HIGH

CHEMWATCH 5072-63
Version No:8.1.1.1
Page 8 of 13

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Amber viscous highly flammable liquid with a strong solvent odour; not miscible with water.

PHYSICAL PROPERTIES

Liquid.
Does not mix with water.
Floats on water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	23	pH (1% solution)	Not Available
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	Not Available	Specific Gravity (water=1)	0.95- 0.98
Lower Explosive Limit (%)	Not Available	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
- Product is considered stable.
- Hazardous polymerisation will not occur.

For incompatible materials - refer to Section 7 - Handling and Storage.

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

■ Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).

Accidental ingestion of the material may be damaging to the health of the individual.

Overexposure to non-ring alcohols causes nervous system symptoms. These include headache, muscle weakness and incoordination, giddiness, confusion, delirium and coma. Digestive symptoms may include nausea, vomiting and diarrhoea. Aspiration is much more dangerous than ingestion because lung damage can occur and the substance is absorbed into the body. Alcohols with ring structures and secondary and tertiary alcohols cause more severe symptoms, as do heavier alcohols.

The main effects of simple esters are irritation, stupor and insensibility. Headache, drowsiness, dizziness, coma and behavioural changes may occur. Respiratory symptoms may include irritation, shortness of breath, rapid breathing, throat inflammation, bronchitis, lung inflammation and pulmonary oedema, sometimes delayed. Nausea, vomiting, diarrhoea and cramps are observed. Liver and kidney damage may result from massive exposures.

EYE

■ If applied to the eyes, this material causes severe eye damage.

SKIN

■ Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

continued...

WATTYL ACID CAT CLEAR PART A

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet
Issue Date: 14-Sep-2013
X9317SP

CHEMWATCH 5072-63
Version No:8.1.1.1
Page 9 of 13

Section 11 - TOXICOLOGICAL INFORMATION

INHALED

■ Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

There is some evidence to suggest that the material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation hazard is increased at higher temperatures.

Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow. Nausea and vomiting are seen, and liver and kidney damage is possible as well following massive exposures. Symptoms are more acute the more carbons there are in the alcohol.

If exposure to highly concentrated solvent atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and possible death.

The main effects of simple esters are irritation, stupor and insensibility. Headache, drowsiness, dizziness, coma and behavioural changes may occur. Respiratory symptoms may include irritation, shortness of breath, rapid breathing, throat inflammation, bronchitis, lung inflammation and pulmonary oedema, sometimes delayed. Nausea, vomiting, diarrhoea and cramps are observed. Liver and kidney damage may result from massive exposures.

CHRONIC HEALTH EFFECTS

■ Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is limited evidence that, skin contact with this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

Prolonged or repeated skin contact may cause drying with cracking, irritation and possible dermatitis following.

Respiratory sensitisation may result in allergic/asthma like responses; from coughing and minor breathing difficulties to bronchitis with wheezing, gasping.

Sensitisation may give severe responses to very low levels of exposure, i.e. hypersensitivity. Sensitised persons should not be allowed to work in situations where exposure may occur.

TOXICITY AND IRRITATION

■ The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

CARCINOGEN

n- propanol	Australia Exposure Standards	Carcinogen Category	Sk	
methyl isobutyl ketone	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	2B	Possibly carcinogenic to humans
n- butanol	Australia Exposure Standards	Carcinogen Category	Sk	
silica amorphous	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3	Not classifiable as to its carcinogenicity to humans

SKIN

n- propanol	Australia Exposure Standards - Skin	Notes	Sk
n- propanol	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1
n- butyl acetate	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	0

continued...

WATTYL ACID CAT CLEAR PART A

Chemwatch Material Safety Data Sheet
 Issue Date: 14-Sep-2013
 X9317SP

Hazard Alert Code: HIGH

CHEMWATCH 5072-63
 Version No:8.1.1.1
 Page 10 of 13

Section 11 - TOXICOLOGICAL INFORMATION

methyl ethyl ketone	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2
methyl isobutyl ketone	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2
n- butanol	Australia Exposure Standards - Skin	Notes	Sk
n- butanol	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2
silica amorphous	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	(0)

Section 12 - ECOLOGICAL INFORMATION

This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
alkyd resin solution	No Data Available	No Data Available	No Data Available	No Data Available
urea/ formaldehyde resin solution, butylated	No Data Available	No Data Available	No Data Available	No Data Available
n- propanol	HIGH	No Data Available	LOW	HIGH
n- butyl acetate	LOW	No Data Available	LOW	HIGH
nitrocellulose with >25% alcohol, <12.6% nitrogen	No Data Available	No Data Available	No Data Available	No Data Available
methyl ethyl ketone	LOW	HIGH	LOW	HIGH
methyl isobutyl ketone	LOW	LOW	LOW	HIGH
n- butanol	LOW	MED	LOW	HIGH
silica amorphous	HIGH	No Data Available	LOW	HIGH

Section 13 - DISPOSAL CONSIDERATIONS

- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID

HAZCHEM:

•3YE (ADG7)

ADG7:

Class or Division:	3	Subsidiary Risk1:	None
UN No.:	1263	Packing Group:	II
Special Provision:	163 *	Limited Quantity:	5 L
Portable Tanks & Bulk	T4	Portable Tanks & Bulk	TP1 TP8

continued...

WATTYL ACID CAT CLEAR PART A

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet

Issue Date: 14-Sep-2013

X9317SP

CHEMWATCH 5072-63

Version No:8.1.1.1

Page 11 of 13

Section 14 - TRANSPORTATION INFORMATION

Containers - Instruction:		Containers - Special Provision:	TP28
Packagings & IBCs - Packing Instruction:	P001 IBC02	Packagings & IBCs - Special Packing Provision:	PP1
Name and Description: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) (see 3.2.5 for relevant [AUST.] entries)			
Air Transport IATA:			
ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1263	Packing Group:	II
Special provisions:	A3A72		
Cargo Only			
Packing Instructions:	364	Maximum Qty/Pack:	60 L
Passenger and Cargo		Passenger and Cargo	
Packing Instructions:	353	Maximum Qty/Pack:	5 L
Passenger and Cargo Limited Quantity		Passenger and Cargo Limited Quantity	
Packing Instructions:	Y341	Maximum Qty/Pack:	1 L

Shipping name:PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Maritime Transport IMDG:

IMDG Class: 3 IMDG Subrisk: None

UN Number: 1263 Packing Group: II

EMS Number: F-E,S-E Special provisions: 163

Limited Quantities: 5 L

Shipping name:PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Section 15 - REGULATORY INFORMATION

Indications of Danger:

F Highly Flammable

Xn Harmful

POISONS SCHEDULE

S5

REGULATIONS

Regulations for ingredients

urea/ formaldehyde resin solution, butylated (CAS: 68002-19-7) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Sigma-AldrichTransport Information"

n-propanol (CAS: 71-23-8) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO", "International Fragrance Association (IFRA) Survey: Transparency List", "IOFI Global Reference List of Chemically Defined Substances", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Sigma-AldrichTransport Information"

n-butyl acetate (CAS: 123-86-4) is found on the following regulatory lists;

"Acros Transport Information", "Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 2", "Australia Exposure Standards", "Australia Hazardous Substances

continued...

Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "IOFI Global Reference List of Chemically Defined Substances", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway", "Sigma-AldrichTransport Information"

methyl ethyl ketone (CAS: 78-93-3) is found on the following regulatory lists;

"Australia Customs (Prohibited Exports) Regulations 1958 - Schedule 9 Precursor substances - Part 2", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Illicit Drug Reagents/Essential Chemicals - Category III", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Fragrance Association (IFRA) Survey: Transparency List", "IOFI Global Reference List of Chemically Defined Substances", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway", "Sigma-AldrichTransport Information", "United Nations Convention Against Illicit Traffic in Narcotic Drugs and Psychotropic Substances - Table II", "United Nations List of Precursors and Chemicals Frequently used in the Illicit Manufacture of Narcotic Drugs and Psychotropic Substances Under International Control (Red List) - Table II"

methyl isobutyl ketone (CAS: 108-10-1) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Fragrance Association (IFRA) Survey: Transparency List", "IOFI Global Reference List of Chemically Defined Substances", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway", "Sigma-AldrichTransport Information"

n-butanol (CAS: 71-36-3) is found on the following regulatory lists;

"Acros Transport Information", "Australia Exposure Standards", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "IOFI Global Reference List of Chemically Defined Substances", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution – Norway", "Sigma-AldrichTransport Information"

silica amorphous (CAS: 7631-86-9, 112945-52-5, 67762-90-7, 68611-44-9, 68909-20-6, 112926-00-8, 61790-53-2, 60676-86-0, 91053-39-3, 69012-64-2, 844491-94-7) is found on the following regulatory lists;

"Acros Transport Information", "Australia - New South Wales - Work Health and Safety Regulation 2011 - Requirements for health monitoring -Hazardous chemicals (other than lead) requiring health monitoring", "Australia - New South Wales - Work Health and Safety Regulation 2011 Restricted hazardous chemicals", "Australia - New South Wales Hazardous Substances Requiring Health Surveillance", "Australia - Northern Territories Work Health and Safety National Uniform Legislation Regulations- Requirements for health monitoring - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - Queensland Work Health and Safety Regulation - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - South Australia - Hazardous Substances Requiring Health Surveillance", "Australia - South Australia - Work Health and Safety Regulations 2012 - Requirements for health monitoring - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - South Australia - Work Health and Safety Regulations 2012 - Restricted hazardous chemicals", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Requirements for Health Monitoring - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Restricted hazardous chemicals", "Australia - Tasmania Hazardous Substances Requiring Health Surveillance", "Australia - Victoria Occupational Health and Safety Regulations - Schedule 5 Hazardous Substances: Substances Prohibited for Specified Uses", "Australia - Western Australia Hazardous Substances Prohibited for Specified Uses or Methods of Handling", "Australia - Western Australia Hazardous Substances Requiring Health Surveillance", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia Occupational Health and Safety

WATTYL ACID CAT CLEAR PART A

Hazard Alert Code: HIGH

Chemwatch Material Safety Data Sheet

Issue Date: 14-Sep-2013

X9317SP

CHEMWATCH 5072-63

Version No:8.1.1.1

Page 13 of 13

Section 15 - REGULATORY INFORMATION

(Commonwealth Employment) (National Standards) Regulations 1994 - Hazardous Substances Requiring Health Surveillance", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix C", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4", "Australia Therapeutic Goods Administration (TGA) Substances that may be used as active ingredients in Listed medicines", "Australia Work Health and Safety Regulations 2011 - Hazardous chemicals (other than lead) requiring health monitoring", "CODEX General Standard for Food Additives (GSFA) - Additives Permitted for Use in Food in General, Unless Otherwise Specified, in Accordance with GMP", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "International Numbering System for Food Additives", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Sigma-AldrichTransport Information"

No data for Watty Acid Cat Clear Part A (CW: 5072-63)

No data for alkyd resin solution (CAS: , Various)

No data for nitrocellulose with >25% alcohol, <12.6% nitrogen (CAS: , Not avail)

Section 16 - OTHER INFORMATION

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
silica amorphous	7631-86-9, 112945-52-5, 67762-90-7, 68611-44-9, 68909-20-6, 112926-00-8, 61790-53-2, 60676-86-0, 91053-39-3, 69012-64-2, 844491-94-7

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 14-Sep-2013

Print Date: 24-Nov-2015

This is the end of the MSDS.