



DESCRIPTION

- exterior durable tinters suitable for use with most Wattyl industrial solvent based finishing systems

PRINCIPAL CHARACTERISTICS

- liquid pigment concentrates designed for use with metered dispensing equipment, and with strength controlled tint bases
- designed to provide an extensive colour offer
- compatible with most Wattyl solvent based paint types, e.g. Acrylic, Epoxy, Alkyd, Copolymer, Acid Cat, Lacquers, Polyurethanes etc. Not suitable for use in water based products.
- Measured quantities of Wattyl Ultratint allows the manufacture of an unlimited range of reproducible colour in a variety of finishes
- Ultratint is suitable only for use with the recommended dispensing and mixing machinery
- lead free
- colour formulations are available from the Wattyl Colour Studio

Note: We advise that you test this product to determine if it is suitable for your particular use.

COLOUR

- White 300, Red 310, Primrose 360, Phthalo Green 370, Orange 410, Black 450, Phthalo Blue 510, Red Oxide 520, Red Violet 530, Medium Yellow 550, Yellow Oxide 560, Bright Yellow 640

INSTRUCTIONS FOR USE

- tinters are dispensed from the recommended dispensing equipment according to the standard formulation, and added directly to the paint being tinted
- once added, the paint and the tinter must be blended together on a tumbling action (gyroscopic) paint shaker for a minimum of five minutes. Failure to blend in this manner may result in an unacceptable finish.
- shelf life (cool, dry place) at least 12 months in unopened container

SAFETY PRECAUTIONS

- flammable. Avoid contact with heat and naked flame
- avoid contact with skin and eyes
- use gloves, mask and goggles during application
- provide adequate ventilation when using in confined spaces
- this product is intended for use in industrial situations by professional applicators in accordance with the advice given on this sheet. All work involving the use and application of this product should be carried out in compliance with all relevant Health, Safety & Environmental standards and regulations and must not be used without reference to the Material Safety Data Sheet (MSDS)

PACKAGING

4 litres

For the most up to date information contact Wattyl Customer Service Hotline or visit the Wattyl Website.

| | | |
|---------------------------------|---|---|
| | Australia | New Zealand |
| CUSTOMER SERVICE HOTLINE | 132 101 | 0800 735 551 |
| WEBSITE | http://www.wattyl.com.au | http://www.wattyl.co.nz |

Wattyl and Ultratint are registered trademarks of Wattyl Australia Pty Ltd.

1. This information is important to ensure that the listed Wattyl product(s) perform according to the stated application and uses and must be followed to meet Wattyl's warranties express and implied. Wattyl advises that you (a) review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) ensure that the product be used only in accordance with the information provided by Wattyl and the product(s) be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (c) thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product. 2. The information in this TDS was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl does not warrant that the information provided is current when the product is used or is wholly comprehensive. 3. For all product and non-product related information, Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl office before using the product(s). 4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product. If coating rectification is required Wattyl Technical Services shall be contacted prior to commencement. WATTYL AUSTRALIA PTY LTD (ABN 40 000 035 914)