



WATTYL WAX & GREASE REMOVER

TM4.10

DESCRIPTION

- a preparatory solvent blend for the removal of wax, grease and other contaminants on metal and previously painted surfaces, prior to coating

PRINCIPAL CHARACTERISTICS

- a blend of special solvents that remove wax and grease without damaging existing paintwork
- suitable for automotive and industrial segments

Note: We advise that you test this product to determine if it is suitable for your particular use.

RECOMMENDED SUBSTRATE CONDITIONS AND TEMPERATURE

- mild steel, non-ferrous metals and previously painted surfaces; prepare surface using the two cloth degreasing technique (below)

INSTRUCTIONS FOR USE

- working in small areas, swab surface liberally with a clean cloth soaked in Wax & Grease Remover, leave in contact with the surface for 1-2 minutes before wiping dry with a new clean cloth (it is essential that clean cloths be changed frequently)
- sand or abrade the surface as required, remove all residue
- repeat the cleaning procedure using the two-cloth degreasing technique as above, before commencing painting

SAFETY PRECAUTIONS

- flammable. Avoid contact with heat and naked flame
- avoid contact with skin and eyes
- use gloves, mask and goggles during application
- provide adequate ventilation when using in confined spaces
- this product is intended for use in industrial situations by professional applicators in accordance with the advice given on this sheet. All work involving the use and application of this product should be carried out in compliance with all relevant Health, Safety & Environmental standards and regulations and must not be used without reference to the Material Safety Data Sheet (MSDS)

PACKAGING

4 litres, 20 litres

For the most up to date information contact Wattyl Customer Service Hotline or visit the Wattyl Website.

	Australia	New Zealand
CUSTOMER SERVICE HOTLINE	132 101	0800 735 551
WEBSITE	http://www.wattyl.com.au	http://www.wattyl.co.nz

Wattyl is a registered trademark of Wattyl Australia Pty Ltd.

1. This information is important to ensure that the listed Wattyl product(s) perform according to the stated application and uses and must be followed to meet Wattyl's warranties express and implied. Wattyl advises that you (a) review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) ensure that the product be used only in accordance with the information provided by Wattyl and the product(s) be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (c) thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product. 2. The information in this TDS was prepared using information gathered during product development. While Wattyl endeavours to update this information and maintain the accuracy and currency of its contents, Wattyl does not warrant that the information provided is current when the product is used or is wholly comprehensive. 3. For all product and non-product related information, Wattyl recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Wattyl office before using the product(s). 4. To the full extent permitted by law, Wattyl's liability for breach of a condition or warranty implied into the contract for sale between Wattyl and you by law is limited at Wattyl's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product. If coating rectification is required Wattyl Technical Services shall be contacted prior to commencement. WATTYL AUSTRALIA PTY LTD (ABN 40 000 035 914)