



DESCRIPTION

- a penetrating clear tung oil modified polyurethane timber coating, for use on interior timber floors where a subdued gloss finish is desired

PRINCIPAL CHARACTERISTICS

- provides a tough protective barrier
- ideally suited for commercial and domestic timber floors
- good wear properties and easy to maintain
- interior use only

Note: We advise that you test this product to determine if it is suitable for your particular use.

COLOUR AND GLOSS

- clear, full gloss 'oiled' appearance

BASIC DATA AT 25° C and 50% RELATIVE HUMIDITY

- touch dry..... 1 hour
- recoat 5 hours
- walk on..... 24 hours (light traffic)
- practical spreading rate 10 m²/L, depending on the surface porosity
- shelf life (cool, dry place) at least 12 months in unopened container

SURFACE PREPARATION

- fill nail holes and minor imperfections with Watty Full Stop Timber Putty. Sand smooth with 100-120 grade paper, and remove all sanding dust
- may be used as self-sealer or alternatively use over Watty Quick Dry Sealer
- not suitable for use with Watty Floor Stain

INSTRUCTIONS FOR USE

- agitate thoroughly with a flat-bladed stirrer before and during use

Timber Floors:

- use a Watty applicator pad or mohair roller
- thinning not usually required, if necessary thin with up to 10% Mineral Turps
- clean up with Mineral Turps

Note: Newly coated floors should be left for 72 hours before finishing with a floor polish

IMPORTANT NOTES REGARDING THE COATING OF TIMBER FLOORS:

- use conventional coating techniques, being prepared to re-sand and re-coat if an adhesion problem arises. (Lack of adhesion is caused by the waxes and oils that may be present naturally in the timber. In extreme cases, peeling can occur.)
- test for satisfactory adhesion by sanding and coating a small test area in advance
- on timbers that occasionally give a problem, fine-sand the surface with 180-240 grade free cut paper, then wash the floor thoroughly with Thinner L743. Completely mop up all residues with a piece of soft cloth
- for recommendations outside those contained in this data sheet, refer to Watty



SAFETY PRECAUTIONS

- flammable. Avoid contact with heat and naked flame
- avoid contact with skin and eyes
- use gloves, mask and goggles during application
- provide adequate ventilation when using in confined spaces
- this product is intended for use in industrial situations by professional applicators in accordance with the advice given on this sheet. All work involving the use and application of this product should be carried out in compliance with all relevant Health, Safety & Environmental standards and regulations and must not be used without reference to the Material Safety Data Sheet (MSDS)

PACKAGING

20 litres

(smaller pack sizes available in the retail range)

For the most up to date information contact Watty Customer Service Hotline or visit the Watty Website.

	Australia	New Zealand
CUSTOMER SERVICE HOTLINE	132 101	0800 735 551
WEBSITE	http://www.watty.com.au	http://www.watty.co.nz

Watty and Estapol are registered trademarks of Watty Australia Pty Ltd.

1. This information is important to ensure that the listed Watty product(s) perform according to the stated application and uses and must be followed to meet Watty's warranties express and implied. Watty advises that you (a) review the Technical Data Sheets (TDS) and Material Safety Data Sheets (MSDS) before you use or handle the product; (b) ensure that the product be used only in accordance with the information provided by Watty and the product(s) be transported, stored and handled in accordance with the information on the MSDS and relevant TDS; and (c) thoroughly test the product, using the recommended application method on a sample of intended substrate, before using the product. 2. The information in this TDS was prepared using information gathered during product development. While Watty endeavours to update this information and maintain the accuracy and currency of its contents, Watty does not warrant that the information provided is current when the product is used or is wholly comprehensive. 3. For all product and non-product related information, Watty recommends that you conduct such additional investigations as may be necessary to satisfy yourself of the accuracy, currency and comprehensiveness of the information on which you rely in using and handling the product. If you require further information please contact your nearest Watty office before using the product(s). 4. To the full extent permitted by law, Watty's liability for breach of a condition or warranty implied into the contract for sale between Watty and you by law is limited at Watty's election to: (a) the replacement of the product; or (b) payment of the cost of replacing the product. If coating rectification is required Watty Technical Services shall be contacted prior to commencement. WATTYL AUSTRALIA PTY LTD (ABN 40 000 035 914)