

Chemwatch Material Safety Data Sheet  
Issue Date: 7-May-2014  
X9317SP

CHEMWATCH 04-0700  
Version No:7.1.1.1  
Page 1 of 13

## Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

### PRODUCT NAME

Wattyl Epinamel PR250 Colours Part A

### PROPER SHIPPING NAME

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

### PRODUCT USE

Used according to manufacturer's directions.

Requires that the two parts be mixed by hand or mixer before use, in accordance with manufacturers directions. Mix only as much as is required. Do not return the mixed material to the original containers.

Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour may displace and replace air in breathing zone, acting as a simple asphyxiant.

### SUPPLIER

Company: Valspar Australia Pty Ltd Pty Limited

Address:

Level 4, 2 Burbank Place

Baulkham Hills

NSW, 2153

Australia

Telephone: +61 2 8867 3333

Emergency Tel: **+61 1800 039 008**

Emergency Tel: **+61 3 9573 3112**

Fax: +61 2 8867 3344

## Section 2 - HAZARDS IDENTIFICATION

### STATEMENT OF HAZARDOUS NATURE

**HAZARDOUS SUBSTANCE. DANGEROUS GOODS.** According to the Criteria of NOHSC, and the ADG Code.

### RISK

Risk Codes	Risk Phrases
R10	• Flammable.
R19	• May form explosive peroxides.
R20/21	• Harmful by inhalation and in contact with skin.
R36/37/38	• Irritating to eyes, respiratory system and skin.
R43	• May cause SENSITISATION by skin contact.
R48/20	• Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R52/53	• Harmful to aquatic organisms, may cause long- term adverse effects in the aquatic environment.
R22?	• Ingestion may produce health damage*.
R33?	• Cumulative effects may result following exposure*.
R40(3)?	• Limited evidence of a carcinogenic effect*.
R42?	• Possible respiratory sensitiser*.
R61?	• May be harmful to the foetus/ embryo*.
R66?	• Repeated exposure potentially causes skin dryness and cracking*.
R67?	• Vapours potentially cause drowsiness and dizziness*.

### SAFETY

Safety Codes	Safety Phrases
S23	• Do not breathe gas/fumes/vapour/spray.
S24	• Avoid contact with skin.
S25	• Avoid contact with eyes.
S36	• Wear suitable protective clothing.
S37	• Wear suitable gloves.
S39	• Wear eye/face protection.

continued...

Chemwatch Material Safety Data Sheet  
Issue Date: 7-May-2014  
X9317SP

CHEMWATCH 04-0700

Version No:7.1.1.1

Page 2 of 13

Section 2 - HAZARDS IDENTIFICATION

S18	• Handle and open container with care.
S51	• Use only in well ventilated areas.
S09	• Keep container in a well ventilated place.
S53	• Avoid exposure - obtain special instructions before use.
S401	• To clean the floor and all objects contaminated by this material, use water and detergent.
S07	• Keep container tightly closed.
S13	• Keep away from food, drink and animal feeding stuffs.
S26	• In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.
S46	• If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
S60	• This material and its container must be disposed of as hazardous waste.
S63	• In case of accident by inhalation: remove casualty to fresh air and keep at rest.

### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
bisphenol A/ diglycidyl ether polymer, high molecular weight	25068-38-6	<20
silica crystalline - quartz	14808-60-7	10-20
xylene	1330-20-7	5-15
n- butanol	71-36-3	1-5
hydrocarbon solvent		1-10
nonylphenol	25154-52-3	<2.5
other ingredients not contributing to the classification		balance

### Section 4 - FIRST AID MEASURES

#### SWALLOWED

- If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Avoid giving milk or oils.
- Avoid giving alcohol.

#### EYE

- If this product comes in contact with the eyes:
  - Wash out immediately with fresh running water.
  - Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
  - Seek medical attention without delay; if pain persists or recurs seek medical attention.
  - Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

#### SKIN

- If skin contact occurs:
  - Immediately remove all contaminated clothing, including footwear.
  - Flush skin and hair with running water (and soap if available).
  - Seek medical attention in event of irritation.

#### INHALED

- If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

continued...

Chemwatch Material Safety Data Sheet  
Issue Date: 7-May-2014  
X9317SP

CHEMWATCH 04-0700

Version No:7.1.1.1

Page 3 of 13

Section 4 - FIRST AID MEASURES

**NOTES TO PHYSICIAN**

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.

Treat symptomatically.

To treat poisoning by the higher aliphatic alcohols (up to C7):

- Gastric lavage with copious amounts of water.
- It may be beneficial to instill 60 ml of mineral oil into the stomach.
- Oxygen and artificial respiration as needed.
- Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.

For acute or short term repeated exposures to xylene:

- Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
- Pulmonary absorption is rapid with about 60-65% retained at rest.
- Primary threat to life from ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases ( $pO_2 < 50$  mm Hg or  $pCO_2 > 50$  mm Hg) should be intubated.

## Section 5 - FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA**

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Do not use a water jet to fight fire.

**FIRE FIGHTING**

- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

**FIRE/EXPLOSION HAZARD**

- Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>), aldehydes, silicon dioxide (SiO<sub>2</sub>), other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

**FIRE INCOMPATIBILITY**

- Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

**HAZCHEM**

•3YE

## Section 6 - ACCIDENTAL RELEASE MEASURES

**MINOR SPILLS**

- Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

**MAJOR SPILLS**

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.

continued...

- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

**Section 7 - HANDLING AND STORAGE**

**PROCEDURE FOR HANDLING**

- Containers, even those that have been emptied, may contain explosive vapours.
  - Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Contains low boiling substance:  
 Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.
- Check for bulging containers.
  - Vent periodically
  - Always release caps or seals slowly to ensure slow dissipation of vapours.
  - DO NOT allow clothing wet with material to stay in contact with skin.
  - Electrostatic discharge may be generated during pumping - this may result in fire.
  - Ensure electrical continuity by bonding and grounding (earthing) all equipment.
  - Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<=1 m/sec until fill pipe submerged to twice its diameter, then <= 7 m/sec).
  - Avoid splash filling.
  - Avoid all personal contact, including inhalation.
  - Wear protective clothing when risk of overexposure occurs.
  - Use in a well-ventilated area.
  - Prevent concentration in hollows and sumps.

**SUITABLE CONTAINER**

- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.

**STORAGE INCOMPATIBILITY**

- Avoid reaction with oxidising agents.

**STORAGE REQUIREMENTS**

- Store in original containers in approved flammable liquid storage area.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.

**Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**EXPOSURE CONTROLS**

Source	Material	TWA ppm	TWA mg/m <sup>3</sup>	STEL ppm	STEL mg/m <sup>3</sup>	Peak ppm	Peak mg/m <sup>3</sup>	TWA F/CC	Notes
Australia Exposure Standards	Wattyl Epinamel PR250 Colours Part A (Xylene (o-, m-, p-isomers))	80		150	655				
Australia Exposure Standards	n- butanol (n- Butyl alcohol)	50							

The following materials had no OELs on our records

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- bisphenol A/ diglycidyl ether polymer, high molecular weight: CAS:25068- 38- 6
- nonylphenol: CAS:25154- 52- 3 CAS:84852- 15- 3 CAS:139- 84- 4 CAS:136- 83- 4

**MATERIAL DATA**

BISPHENOL A/ DIGLYCIDYL ETHER POLYMER, HIGH MOLECULAR WEIGHT:  
 N-BUTANOL:

WATTYL EPINAMEL PR250 COLOURS PART A:

For n-butanol:

Odour Threshold Value: 0.12-3.4 ppm (detection), 1.0-3.5 ppm (recognition)

NOTE: Detector tubes for n-butanol, measuring in excess of 5 ppm are commercially available.

Exposure at or below the TLV-TWA is thought to provide protection against hearing loss due to vestibular and auditory nerve damage in younger workers and to protect against the significant risk of headache and irritation.

25 ppm may produce mild irritation of the respiratory tract 50 ppm may produce headache and vertigo.

Higher concentrations may produce marked irritation, sore throat, coughing, nausea, shortness of breath, pulmonary injury and central nervous system depression characterised by headache, dizziness, dullness and drowsiness.

SILICA CRYSTALLINE - QUARTZ:

WATTYL EPINAMEL PR250 COLOURS PART A:

Because the margin of safety of the quartz TLV is not known with certainty and given the associated link between silicosis and lung cancer it is recommended that quartz concentrations be maintained as far below the TLV as prudent practices will allow.

Exposure to respirable crystalline silicas (RCS) represents a significant hazard to workers, particularly those employed in the construction industry where respirable dusts of cement and concrete are common.

WATTYL EPINAMEL PR250 COLOURS PART A:

XYLENE:

for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).

SILICA CRYSTALLINE - QUARTZ:

WATTYL EPINAMEL PR250 COLOURS PART A:

The concentration of dust, for application of respirable dust limits, is to be determined from the fraction that penetrates a separator whose size collection efficiency is described by a cumulative log-normal function with a median aerodynamic diameter of 4.0 µm (+) 0.3 µm and with a geometric standard deviation of 1.5 µm (+) 0.1 µm, i.e. generally less than 5 µm.

SILICA CRYSTALLINE - QUARTZ:

WATTYL EPINAMEL PR250 COLOURS PART A:

WARNING: For inhalation exposure ONLY: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS.

SILICA CRYSTALLINE - QUARTZ:

WATTYL EPINAMEL PR250 COLOURS PART A:

The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 µm) crystalline silica as being carcinogenic to humans. This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite.

Intermittent exposure produces; focal fibrosis, (pneumoconiosis), cough, dyspnoea, liver tumours.

BISPHENOL A/ DIGLYCIDYL ETHER POLYMER, HIGH MOLECULAR WEIGHT:

For epichlorohydrin

Odour Threshold Value: 0.08 ppm

NOTE: Detector tubes for epichlorohydrin, measuring in excess of 5 ppm, are commercially available.

Exposure at or below the recommended TLV-TWA is thought to minimise the potential for adverse respiratory, liver, kidney effects.

Odour Safety Factor (OSF)

OSF=0.54 (EPICHLOROHYDRIN).

For toluene:

Odour Threshold Value: 0.16-6.7 (detection), 1.9-69 (recognition)

NOTE: Detector tubes measuring in excess of 5 ppm, are available.

High concentrations of toluene in the air produce depression of the central nervous system (CNS) in humans.

SILICA CRYSTALLINE - QUARTZ:

WARNING: For inhalation exposure ONLY:

This substance has been classified by the ACGIH as A2 Suspected Human Carcinogen.

Chemwatch Material Safety Data Sheet  
Issue Date: 7-May-2014  
X9317SP

CHEMWATCH 04-0700  
Version No:7.1.1.1  
Page 6 of 13

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

**XYLENE:**

Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

**N-BUTANOL:**

Exposed individuals are reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class A or B.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

Class	OSF	Description
A	550	Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV- TWA for example) is being reached, even when distracted by working activities
B	26- 550	As " A" for 50- 90% of persons being distracted
C	1- 26	As " A" for less than 50% of persons being distracted
D	0.18- 1	10- 50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached
E	<0.18	As " D" for less than 10% of persons aware of being tested

**NONYLPHENOL:**

Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

**PERSONAL PROTECTION****RESPIRATOR**

•Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

**EYE**

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

**HANDS/FEET****■ NOTE:**

- The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:.

- When handling liquid-grade epoxy resins wear chemically protective gloves (e.g nitrile or nitrile-butatoluene rubber), boots

continued...

# Wattyl Epinamel PR250 Colours Part A

Hazard Alert Code: **EXTREME**

Chemwatch Material Safety Data Sheet  
Issue Date: 7-May-2014  
X9317SP

CHEMWATCH 04-0700  
Version No:7.1.1.1  
Page 7 of 13

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

- and aprons.
- DO NOT use cotton or leather (which absorb and concentrate the resin), polyvinyl chloride, rubber or polyethylene gloves (which absorb the resin).
- DO NOT use barrier creams containing emulsified fats and oils as these may absorb the resin; silicone-based barrier creams should be reviewed prior to use.

### OTHER

- Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

### ENGINEERING CONTROLS

■ Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

## Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE

Coloured flammable liquid with a solvent odour; not miscible with water.

### PHYSICAL PROPERTIES

Liquid.			
Does not mix with water.			
Sinks in water.			
State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	Not Available	Solubility in water (g/L)	Immiscible
Flash Point (°C)	27	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	Not Available	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	35.4	Specific Gravity (water=1)	>1
Lower Explosive Limit (%)	4.2	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	Not Available	Evaporation Rate	Not Available

## Section 10 - STABILITY AND REACTIVITY

### CONDITIONS CONTRIBUTING TO INSTABILITY

- Presence of incompatible materials.
  - Product is considered stable.
  - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

continued...

Chemwatch Material Safety Data Sheet  
Issue Date: 7-May-2014  
X9317SP

CHEMWATCH 04-0700  
Version No:7.1.1.1  
Page 8 of 13

## Section 11 - TOXICOLOGICAL INFORMATION

### POTENTIAL HEALTH EFFECTS

#### ACUTE HEALTH EFFECTS

##### SWALLOWED

■ Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).

Accidental ingestion of the material may be damaging to the health of the individual.

Overexposure to non-ring alcohols causes nervous system symptoms. These include headache, muscle weakness and incoordination, giddiness, confusion, delirium and coma. Digestive symptoms may include nausea, vomiting and diarrhoea. Aspiration is much more dangerous than ingestion because lung damage can occur and the substance is absorbed into the body. Alcohols with ring structures and secondary and tertiary alcohols cause more severe symptoms, as do heavier alcohols.

##### EYE

■ There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain. There may be damage to the cornea. Unless treatment is prompt and adequate there may be permanent loss of vision. Conjunctivitis can occur following repeated exposure.

##### SKIN

■ Skin contact with the material may be harmful; systemic effects may result following absorption.

The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.

Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man.

Open cuts, abraded or irritated skin should not be exposed to this material.

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.

Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

##### INHALED

■ Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.

Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

The acute toxicity of inhaled alkylbenzenes is best described by central nervous system depression. As a rule, these compounds may also act as general anaesthetics.

Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow. Nausea and vomiting are seen, and liver and kidney damage is possible as well following massive exposures. Symptoms are more acute the more carbons there are in the alcohol.

Material is highly volatile and may quickly form a concentrated atmosphere in confined or unventilated areas. The vapour displace and replace air in breathing zone, acting as a simple asphyxiant.

Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

#### CHRONIC HEALTH EFFECTS

■ Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. This has been demonstrated via both short- and long-term experimentation.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

There is some evidence from animal testing that exposure to this material may result in toxic effects to the unborn baby.

Women exposed to xylene in the first 3 months of pregnancy showed a slightly increased risk of miscarriage and birth defects.

Evaluation of workers chronically exposed to xylene has demonstrated lack of genetic toxicity. Exposure to xylene has been associated with increased rates of blood cancer, but this may be complicated by exposure to other substances, including benzene.

Animal testing found no evidence of cancer-causing activity.

continued...



There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

**TOXICITY AND IRRITATION**

■ The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Oxiranes (including glycidyl ethers and alkyl oxides, and epoxides) exhibit many common characteristics with respect to animal toxicology. One such oxirane is ethyloxirane; data presented here may be taken as representative. for 1,2-butylene oxide (ethyloxirane): Ethyloxirane increased the incidence of tumours of the respiratory system in male and female rats exposed via inhalation. Significant increases in nasal papillary adenomas and combined alveolar/bronchiolar adenomas and carcinomas were observed in male rats exposed to 1200 mg/m3 ethyloxirane via inhalation for 103 weeks.

**CARCINOGEN**

silica crystalline - quartz	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	1	Carcinogenic to humans
xylene	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3	Not classifiable as to its carcinogenicity to humans
n- butanol	Australia Exposure Standards	Carcinogen Category	Sk	

**SKIN**

xylene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2
xylene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1
n- butanol	Australia Exposure Standards - Skin	Notes	Sk
n- butanol	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2
nonylphenol	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	3

**Section 12 - ECOLOGICAL INFORMATION**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. This material and its container must be disposed of as hazardous waste.

**Ecotoxicity**  
 Ingredient

Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
-------------------------	------------------	-----------------	----------

# Watty Epinamel PR250 Colours Part A

**Hazard Alert Code: EXTREME**

**Chemwatch Material Safety Data Sheet**  
**Issue Date: 7-May-2014**  
**X9317SP**

**CHEMWATCH 04-0700**  
**Version No:7.1.1.1**  
**Page 10 of 13**

**Section 12 - ECOLOGICAL INFORMATION**

bisphenol A/ diglycidyl ether polymer, high molecular weight silica crystalline - quartz	No Data Available No Data Available	No Data Available No Data Available	No Data Available No Data Available	No Data Available No Data Available
xylene	LOW	LOW	LOW	No Data Available
n- butanol	LOW	MED	LOW	HIGH
nonylphenol	HIGH	No Data Available	LOW	LOW

**Section 13 - DISPOSAL CONSIDERATIONS**

- Containers may still present a chemical hazard/ danger when empty.
  - Return to supplier for reuse/ recycling if possible.
  - Otherwise:
    - If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
    - Where possible retain label warnings and MSDS and observe all notices pertaining to the product.
- Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.
- A Hierarchy of Controls seems to be common - the user should investigate:
- Reduction.
  - DO NOT allow wash water from cleaning or process equipment to enter drains.
  - It may be necessary to collect all wash water for treatment before disposal.
  - In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
  - Where in doubt contact the responsible authority.
  - Recycle wherever possible.
  - Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
  - Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).
  - Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

**Section 14 - TRANSPORTATION INFORMATION**

Labels Required: FLAMMABLE LIQUID

**HAZCHEM:**  
 •3YE (ADG7)

**ADG7:**

Class or Division:	3	Subsidiary Risk1:	None
UN No.:	1263	Packing Group:	III
Special Provision:	163 223 *	Limited Quantity:	5 L
Portable Tanks & Bulk	T2	Portable Tanks & Bulk	TP1 TP29
Containers - Instruction:		Containers - Special Provision:	

Packagings & IBCs - Packing Instruction:	P001 IBC03 LP01	Packagings & IBCs - Special Packing Provision:	PP1
--	-----------------	--	-----

Name and Description: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound) (see 3.2.5 for relevant [AUST.] entries)

**Air Transport IATA:**

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1263	Packing Group:	III
Special provisions:	A3A72		
Cargo Only			
Packing Instructions: Passenger and Cargo	366	Maximum Qty/Pack:	220 L
Packing Instructions: Passenger and Cargo Limited Quantity	355	Maximum Qty/Pack:	60 L

**continued...**

# Wattyl Epinamel PR250 Colours Part A

Hazard Alert Code: **EXTREME**

Chemwatch Material Safety Data Sheet  
Issue Date: 7-May-2014  
X9317SP

CHEMWATCH 04-0700  
Version No:7.1.1.1  
Page 11 of 13

## Section 14 - TRANSPORTATION INFORMATION

Packing Instructions: Y344 Maximum Qty/Pack: 10 L

Shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

### Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	III
EMS Number:	F-E,S-E	Special provisions:	163 223 955
Limited Quantities:	5 L		

Shipping name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

## Section 15 - REGULATORY INFORMATION

### Indications of Danger:

Xn Harmful

### POISONS SCHEDULE

S5

### REGULATIONS

#### Wattyl Epinamel PR250 Colours Part A (CAS: ) is found on the following regulatory lists;

"Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "OECD List of High Production Volume (HPV) Chemicals", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

#### Regulations for ingredients

#### bisphenol A/ diglycidyl ether polymer, high molecular weight (CAS: 25068-38-6) is found on the following regulatory lists;

"Australia - Victoria Occupational Health and Safety Regulations - Schedule 9: Materials at Major Hazard Facilities (And Their Threshold Quantity) Table 2", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-Aldrich Transport Information"

#### silica crystalline - quartz (CAS: 14808-60-7, 122304-48-7, 122304-49-8, 12425-26-2, 1317-79-9, 70594-95-5, 87347-84-0) is found on the following regulatory lists;

"Australia - New South Wales - Work Health and Safety Regulation 2011 - Requirements for health monitoring - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - New South Wales - Work Health and Safety Regulation 2011 Restricted hazardous chemicals", "Australia - New South Wales Hazardous Substances Prohibited for Specific Uses", "Australia - New South Wales Hazardous Substances Requiring Health Surveillance", "Australia - Northern Territories Work Health and Safety National Uniform Legislation Regulations- Requirements for health monitoring - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - Northern Territories Work Health and Safety National Uniform Legislation Regulations- Restricted hazardous chemicals", "Australia - Queensland Work Health and Safety Regulation - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - Queensland Work Health and Safety Regulation - Restricted hazardous chemicals", "Australia - South Australia - Hazardous Substances Requiring Health Surveillance", "Australia - South Australia - Work Health and Safety Regulations 2012 - Requirements for health monitoring - Hazardous chemicals (other than lead) requiring health monitoring",

continued...

Chemwatch Material Safety Data Sheet  
Issue Date: 7-May-2014  
X9317SP

CHEMWATCH 04-0700

Version No:7.1.1.1

Page 12 of 13

Section 15 - REGULATORY INFORMATION

"Australia - South Australia - Work Health and Safety Regulations 2012 - Restricted hazardous chemicals", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Requirements for Health Monitoring - Hazardous chemicals (other than lead) requiring health monitoring", "Australia - Tasmania - Work Health and Safety Regulations 2012 - Restricted hazardous chemicals", "Australia - Tasmania Hazardous Substances Prohibited for Specified Uses", "Australia - Tasmania Hazardous Substances Requiring Health Surveillance", "Australia - Western Australia Hazardous Substances Prohibited for Specified Uses or Methods of Handling", "Australia - Western Australia Hazardous Substances Requiring Health Surveillance", "Australia Exposure Standards", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia Hazardous Substances Requiring Health Surveillance", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia Occupational Health and Safety (Commonwealth Employment) (National Standards) Regulations 1994 - Hazardous Substances Requiring Health Surveillance", "Australia Work Health and Safety Regulations 2011 - Hazardous chemicals (other than lead) requiring health monitoring", "Australia Work Health and Safety Regulations 2011 - Restricted hazardous chemicals", "FisherTransport Information", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "OECD List of High Production Volume (HPV) Chemicals", "Sigma-AldrichTransport Information", "United Nations Consolidated List of Products Whose Consumption and/or Sale Have Been Banned, Withdrawn, Severely Restricted or Not Approved by Governments"

**xylene (CAS: 1330-20-7) is found on the following regulatory lists;**

"Australia - Australian Capital Territory - Environment Protection Regulation: Ambient environmental standards (Domestic water supply - organic compounds)", "Australia - Australian Capital Territory - Environment Protection Regulation: Pollutants entering waterways taken to cause environmental harm - Domestic water supply quality", "Australia Drinking Water Guideline Values For Physical and Chemical Characteristics", "Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Chemicals for Priority Action", "WHO Guidelines for Drinking-water Quality - Guideline values for chemicals that are of health significance in drinking-water"

**n-butanol (CAS: 71-36-3) is found on the following regulatory lists;**

"Acros Transport Information", "Australia Exposure Standards", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia High Volume Industrial Chemical List (HVICL)", "Australia Inventory of Chemical Substances (AICS)", "Australia National Pollutant Inventory", "FisherTransport Information", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO IBC Code Chapter 18: List of products to which the Code does not apply", "IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances", "International Council of Chemical Associations (ICCA) - High Production Volume List", "International Fragrance Association (IFRA) Survey: Transparency List", "IOFI Global Reference List of Chemically Defined Substances", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR National List of Candidates for Substitution - Norway", "Sigma-AldrichTransport Information"

**nonylphenol (CAS: 25154-52-3, 84852-15-3, 139-84-4, 136-83-4) is found on the following regulatory lists;**

"Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Hazardous Substances Information System - Consolidated Lists", "Australia Inventory of Chemical Substances (AICS)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2", "GESAMP/EHS Composite List - GESAMP Hazard Profiles", "IMO IBC Code Chapter 17: Summary of minimum requirements", "IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk", "International Chemical Secretariat (ChemSec) SIN List (\*Substitute It Now!)", "International Fragrance Association (IFRA) Survey: Transparency List", "International Maritime Dangerous Goods Requirements (IMDG Code) - Marine Pollutants", "OECD List of High Production Volume (HPV) Chemicals", "OSPAR List of Substances of Possible Concern", "Sigma-AldrichTransport Information", "United Nations Consolidated List of Products Whose Consumption and/or Sale Have Been Banned, Withdrawn, Severely Restricted or Not Approved by Governments"

**No data for Solvent 100 (CW: 4687-52)**

Chemwatch Material Safety Data Sheet  
Issue Date: 7-May-2014  
X9317SP

CHEMWATCH 04-0700  
Version No:7.1.1.1  
Page 13 of 13

## Section 16 - OTHER INFORMATION

### Denmark Advisory list for selfclassification of dangerous substances

Substance	CAS	Suggested codes
nonylphenol	25154- 52- 3	R43
nonylphenol	139- 84- 4	Xn; R22 R43 N; R50/53
nonylphenol	136- 83- 4	R43

### INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
silica crystalline - quartz	14808-60-7, 122304-48-7, 122304-49-8, 12425-26-2, 1317-79-9, 70594-95-5, 87347-84-0
nonylphenol	25154-52-3, 84852-15-3, 139-84-4, 136-83-4

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net/references](http://www.chemwatch.net/references).

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

*This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.*

Issue Date: 7-May-2014  
Print Date: 14-May-2015

*This is the end of the MSDS.*