

WATTYL POLY U400 MCR PART A

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Aug-2013

9317SP(cs)

CHEMWATCH 460365

Version No:10.1.1.1

CD 2013/2 Page 1 of 10

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME

WATTYL POLY U400 MCR PART A

SYNONYMS

"Product Code: 202201, 202204, 202207", "202210, 202216, 202222, 202225", 202228

PROPER SHIPPING NAME

PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)

PRODUCT USE

■ Used according to manufacturer's directions.

Requires that the two parts be mixed by hand or mixer before use, in accordance with manufacturers directions. Mix only as much as is required. Do not return the mixed material to the original containers.

Refer also to protective measures for the other component used with the product. Read both MSDS before using; store and attach MSDS together.

CONTAINS free organic isocyanate. Mixing and application requires special precautions and use of personal protective gear [APMF].

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

SUPPLIER

Company: Valspar Australia Pty Ltd Pty Limited

Address:

Level 4, 2 Burbank Place

Baulkham Hills

NSW, 2153

Australia

Telephone: +61 2 8867 3333

Emergency Tel:+61 1800 039 008

Emergency Tel:+61 3 9573 3112

Fax: +61 2 8867 3344

Section 2 - HAZARDS IDENTIFICATION

STATEMENT OF HAZARDOUS NATURE

HAZARDOUS SUBSTANCE. DANGEROUS GOODS. According to the Criteria of NOHSC, and the ADG Code.

RISK

Risk Codes

R10

R20/21

R36/37/38

R52/53

R67

Risk Phrases

• Flammable.

• Harmful by inhalation and in contact with skin.

• Irritating to eyes, respiratory system and skin.

• Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

• Vapours may cause drowsiness and dizziness.

SAFETY

Safety Codes

S23

S24

S25

S36

S37

S39

S51

S09

S401

Safety Phrases

• Do not breathe gas/fumes/vapour/spray.

• Avoid contact with skin.

• Avoid contact with eyes.

• Wear suitable protective clothing.

• Wear suitable gloves.

• Wear eye/face protection.

• Use only in well ventilated areas.

• Keep container in a well ventilated place.

• To clean the floor and all objects contaminated by this material, use water and detergent.

S07

• Keep container tightly closed.

S13

• Keep away from food, drink and animal feeding stuffs.

S26

• In case of contact with eyes, rinse with plenty of water and contact Doctor or Poisons Information Centre.

continued...

WATTYL POLY U400 MCR PART A

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Aug-2013

9317SP(cs)

CHEMWATCH 460365

Version No:10.1.1.1

CD 2013/2 Page 2 of 10

Section 2 - HAZARDS IDENTIFICATION

- S46 • If swallowed, IMMEDIATELY contact Doctor or Poisons Information Centre. (show this container or label).
- S60 • This material and its container must be disposed of as hazardous waste.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

NAME	CAS RN	%
xylene	1330-20-7	10-20
naphtha solvent alkyl ester		10-20
titanium dioxide	13463-67-7	<5
hydrocarbon solvent		0-20
propylene glycol monomethyl ether acetate, alpha- isomer	108-65-6	<5
methyl 1, 2, 2, 6, 6- pentamethyl- 4- piperidyl sebacate	82919-37-7	<5
other ingredients not contributing to the classification		<0.1
		balance

Section 4 - FIRST AID MEASURES

SWALLOWED

- - If swallowed do NOT induce vomiting.
- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Avoid giving milk or oils.
- Avoid giving alcohol.
- If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

EYE

- If this product comes in contact with the eyes:
- Wash out immediately with fresh running water.
- Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
- Seek medical attention without delay; if pain persists or recurs seek medical attention.
- Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

SKIN

- If skin contact occurs:
- Immediately remove all contaminated clothing, including footwear.
- Flush skin and hair with running water (and soap if available).
- Seek medical attention in event of irritation.

INHALED

- - If fumes or combustion products are inhaled remove from contaminated area.
- Lay patient down. Keep warm and rested.
- Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
- Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

NOTES TO PHYSICIAN

- Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically.
- For acute or short term repeated exposures to xylene:
- Gastro-intestinal absorption is significant with ingestions. For ingestions exceeding 1-2 ml (xylene)/kg, intubation and lavage with cuffed endotracheal tube is recommended. The use of charcoal and cathartics is equivocal.
 - Pulmonary absorption is rapid with about 60-65% retained at rest.
 - Primary threat to life from ingestion and/or inhalation, is respiratory failure.
 - Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO₂ < 50 mm Hg or pCO₂ > 50 mm Hg) should be intubated.

continued...

WATTYL POLY U400 MCR PART A

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Aug-2013

9317SP(cs)

CHEMWATCH 460365

Version No:10.1.1.1

CD 2013/2 Page 3 of 10

Section 5 - FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

- - Water spray or fog.
 - Alcohol stable foam.
 - Dry chemical powder.
 - Carbon dioxide.
- Do not use a water jet to fight fire.

FIRE FIGHTING

- - Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.
- Prevent, by any means available, spillage from entering drains or water course.

FIRE/EXPLOSION HAZARD

- - Liquid and vapour are flammable.
- Moderate fire hazard when exposed to heat or flame.
- Vapour forms an explosive mixture with air.
- Moderate explosion hazard when exposed to heat or flame.

Combustion products include: carbon monoxide (CO), carbon dioxide (CO₂), other pyrolysis products typical of burning organic material.

Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.

FIRE INCOMPATIBILITY

- - Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result.

HAZCHEM

•3Y

Section 6 - ACCIDENTAL RELEASE MEASURES

MINOR SPILLS

- - Remove all ignition sources.
- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.

MAJOR SPILLS

- - Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- May be violently or explosively reactive.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

Section 7 - HANDLING AND STORAGE

PROCEDURE FOR HANDLING

- - Containers, even those that have been emptied, may contain explosive vapours.
 - Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Contains low boiling substance:
Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately.
- Check for bulging containers.
 - Vent periodically
 - Always release caps or seals slowly to ensure slow dissipation of vapours.
 - DO NOT allow clothing wet with material to stay in contact with skin.
 - Electrostatic discharge may be generated during pumping - this may result in fire.
 - Ensure electrical continuity by bonding and grounding (earthing) all equipment.
 - Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/sec until fill pipe submerged to twice its diameter, then ≤ 7 m/sec).
 - Avoid splash filling.
 - Avoid all personal contact, including inhalation.

continued...

WATTYL POLY U400 MCR PART A

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Aug-2013

9317SP(cs)

CHEMWATCH 460365

Version No:10.1.1.1

CD 2013/2 Page 4 of 10

Section 7 - HANDLING AND STORAGE

- Wear protective clothing when risk of overexposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps.

SUITABLE CONTAINER

- - Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
- Check that containers are clearly labelled and free from leaks.
- For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.
- For materials with a viscosity of at least 2680 cSt. (23 deg. C)
- For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)
- Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.

STORAGE INCOMPATIBILITY

- - Avoid reaction with oxidising agents.

STORAGE REQUIREMENTS

- - Store in original containers in approved flammable liquid storage area.
- Store away from incompatible materials in a cool, dry, well-ventilated area.
- DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- No smoking, naked lights, heat or ignition sources.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE CONTROLS

Source	Material	TWA ppm	STEL ppm	STEL mg/m ³	Notes
Australia Exposure Standards	(Xylene (o-, m-, p-isomers))	80	150	655	NOHSC documentation available for these values.
Australia Exposure Standards	(1- Methoxy- 2-propanol acetate)	50	100	548	

The following materials had no OELs on our records

- methyl 1, 2, 2, 6, 6- pentamethyl- 4- piperidyl sebacate: CAS:82919- 37- 7

MATERIAL DATA

PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE, ALPHA-ISOMER:

WATTYL POLY U400 MCR PART A:

- for propylene glycol monomethyl ether acetate (PGMEA)

Saturated vapour concentration: 4868 ppm at 20 C.

A two-week inhalation study found nasal effects to the nasal mucosa in animals at concentrations up to 3000 ppm.

TITANIUM DIOXIDE:

WATTYL POLY U400 MCR PART A:

- Animals exposed by inhalation to 10 mg/m³ titanium dioxide show no significant fibrosis, possibly reversible tissue reaction. The architecture of lung air spaces remains intact.

WATTYL POLY U400 MCR PART A:

XYLENE:

- for xylenes:

IDLH Level: 900 ppm

Odour Threshold Value: 20 ppm (detection), 40 ppm (recognition)

NOTE: Detector tubes for o-xylene, measuring in excess of 10 ppm, are available commercially. (m-xylene and p-xylene give almost the same response).<</>

WATTYL POLY U400 MCR PART A:

- For n-butyl acetate

Odour Threshold Value: 0.0063 ppm (detection), 0.038-12 ppm (recognition)

Exposure at or below the recommended TLV-TWA is thought to prevent significant irritation of the eyes and respiratory passages as well as narcotic effects. In light of the lack of substantive evidence regarding teratogenicity and a review of acute oral data a STEL is considered inappropriate.

Odour Safety Factor(OSF)

continued...

WATTYL POLY U400 MCR PART A

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Aug-2013

9317SP(cs)

CHEMWATCH 460365

Version No:10.1.1.1

CD 2013/2 Page 5 of 10

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

OSF=3.8E2 (n-BUTYL ACETATE).

XYLENE:

■ Exposure limits with "skin" notation indicate that vapour and liquid may be absorbed through intact skin. Absorption by skin may readily exceed vapour inhalation exposure. Symptoms for skin absorption are the same as for inhalation. Contact with eyes and mucous membranes may also contribute to overall exposure and may also invalidate the exposure standard.

TITANIUM DIOXIDE:

■ Sensory irritants are chemicals that produce temporary and undesirable side-effects on the eyes, nose or throat. Historically occupational exposure standards for these irritants have been based on observation of workers' responses to various airborne concentrations.

METHYL 1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL SEBACATE:

CEL TWA: 1 mg/m³ (Ciba)

PERSONAL PROTECTION

RESPIRATOR

• Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

EYE

■ - Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lens or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent].

HANDS/FEET

■ - Wear chemical protective gloves, e.g. PVC.
- Wear safety footwear or safety gumboots, e.g. Rubber.
The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

OTHER

■ - Overalls.
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets), non sparking safety footwear.

ENGINEERING CONTROLS

■ When spraying the MIXED material use a positive air pressure, air supplied full face respirator while spraying and until spray mist has been effectively dispersed.
Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
The basic types of engineering controls are:
Process controls which involve changing the way a job activity or process is done to reduce the risk.
Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Coloured flammable liquid with a strong solvent odour; does not mix with water.

continued...

WATTYL POLY U400 MCR PART A

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Aug-2013

9317SP(cs)

CHEMWATCH 460365

Version No:10.1.1.1

CD 2013/2 Page 6 of 10

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL PROPERTIES

Liquid.
Does not mix with water.
Sinks in water.

State	Liquid	Molecular Weight	Not Applicable
Melting Range (°C)	Not Available	Viscosity	Not Available
Boiling Range (°C)	128- 175	Solubility in water (g/L)	Immiscible
Flash Point (°C)	28 (OC- lit)	pH (1% solution)	Not Applicable
Decomposition Temp (°C)	Not Available	pH (as supplied)	Not Applicable
Autoignition Temp (°C)	426	Vapour Pressure (kPa)	Not Available
Upper Explosive Limit (%)	7.0	Specific Gravity (water=1)	1.0- 1.3
Lower Explosive Limit (%)	1.0	Relative Vapour Density (air=1)	>1
Volatile Component (%vol)	10- 30	Evaporation Rate	Not Available

Section 10 - STABILITY AND REACTIVITY

CONDITIONS CONTRIBUTING TO INSTABILITY

- - Presence of incompatible materials.
 - Product is considered stable.
 - Hazardous polymerisation will not occur.
- For incompatible materials - refer to Section 7 - Handling and Storage.*

Section 11 - TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS

ACUTE HEALTH EFFECTS

SWALLOWED

- Accidental ingestion of the material may be damaging to the health of the individual.
- Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733).
- Ingestion of petroleum hydrocarbons can irritate the pharynx, oesophagus, stomach and small intestine, and cause swellings and ulcers of the mucous. Symptoms include a burning mouth and throat; larger amounts can cause nausea and vomiting, narcosis, weakness, dizziness, slow and shallow breathing, abdominal swelling, unconsciousness and convulsions. Damage to the heart muscle can produce heart beat irregularities, ventricular fibrillation (fatal) and ECG changes. The central nervous system can be depressed. Light species can cause a sharp tingling of the tongue and cause loss of sensation there. Aspiration can cause cough, gagging, pneumonia with swelling and bleeding.

EYE

- This material can cause eye irritation and damage in some persons.
- Direct eye contact with petroleum hydrocarbons can be painful, and the corneal epithelium may be temporarily damaged. Aromatic species can cause irritation and excessive tear secretion.

SKIN

- Skin contact with the material may be harmful; systemic effects may result following absorption.
- This material can cause inflammation of the skin on contact in some persons.
- The material may accentuate any pre-existing dermatitis condition.
- Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.
- Open cuts, abraded or irritated skin should not be exposed to this material.
- Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects.
- Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

INHALED

- Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.
- The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
- Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.
- The acute toxicity of inhaled alkylbenzenes is best described by central nervous system depression. As a rule, these compounds may also act as general anaesthetics.
- Inhalation hazard is increased at higher temperatures.
- Inhaling high concentrations of mixed hydrocarbons can cause narcosis, with nausea, vomiting and lightheadedness. Low molecular

continued...

WATTYL POLY U400 MCR PART A

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Aug-2013

9317SP(cs)

CHEMWATCH 460365

Version No:10.1.1.1

CD 2013/2 Page 7 of 10

Section 11 - TOXICOLOGICAL INFORMATION

weight (C2-C12) hydrocarbons can irritate mucous membranes and cause incoordination, giddiness, nausea, vertigo, confusion, headache, appetite loss, drowsiness, tremors and stupor. Massive exposures can lead to severe central nervous system depression, deep coma and death. Convulsions can occur due to brain irritation and/or lack of oxygen. Permanent scarring may occur, with epileptic seizures and brain bleeds occurring months after exposure. Respiratory system effects include inflammation of the lungs with oedema and bleeding. Lighter species mainly cause kidney and nerve damage; the heavier paraffins and olefins are especially irritant to the respiratory system. Alkenes produce pulmonary oedema at high concentrations. Liquid paraffins may produce sensation loss and depressant actions leading to weakness, dizziness, slow and shallow respiration, unconsciousness, convulsions and death. C5-7 paraffins may also produce multiple nerve damage. Aromatic hydrocarbons accumulate in lipid rich tissues (typically the brain, spinal cord and peripheral nerves) and may produce functional impairment manifested by nonspecific symptoms such as nausea, weakness, fatigue, vertigo; severe exposures may produce inebriation or unconsciousness. Many of the petroleum hydrocarbons can sensitise the heart and may cause ventricular fibrillation, leading to death. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination.

CHRONIC HEALTH EFFECTS

■ Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Constant or exposure over long periods to mixed hydrocarbons may produce stupor with dizziness, weakness and visual disturbance, weight loss and anaemia, and reduced liver and kidney function. Skin exposure may result in drying and cracking and redness of the skin. Chronic exposure to lighter hydrocarbons can cause nerve damage, peripheral neuropathy, bone marrow dysfunction and psychiatric disorders as well as damage the liver and kidneys.

Women exposed to xylene in the first 3 months of pregnancy showed a slightly increased risk of miscarriage and birth defects.

Evaluation of workers chronically exposed to xylene has demonstrated lack of genetic toxicity. Exposure to xylene has been associated with increased rates of blood cancer, but this may be complicated by exposure to other substances, including benzene.

Animal testing found no evidence of cancer-causing activity.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).

Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material.

Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS].

TOXICITY AND IRRITATION

■ Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound.

No significant acute toxicological data identified in literature search.

CARCINOGEN

xylene	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	3	Not classifiable as to its carcinogenicity to humans
titanium dioxide	International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs	Group	2B	Possibly carcinogenic to humans
propylene glycol monomethyl ether acetate, alpha-isomer	Australia Exposure Standards	Carcinogen Category	Sk	

SKIN

xylene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	2
xylene	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1
titanium dioxide	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	1
propylene glycol monomethyl ether acetate, alpha-isomer	Australia Exposure Standards - Skin	Notes	Sk

continued...

WATTYL POLY U400 MCR PART A

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Aug-2013

9317SP(cs)

CHEMWATCH 460365

Version No:10.1.1.1

CD 2013/2 Page 8 of 10

Section 11 - TOXICOLOGICAL INFORMATION

propylene glycol monomethyl ether acetate, alpha-isomer	GESAMP/EHS Composite List - GESAMP Hazard Profiles	D1: skin irritation/corrosion	0
---	--	-------------------------------	---

Section 12 - ECOLOGICAL INFORMATION

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. This material and its container must be disposed of as hazardous waste.

Ecotoxicity

Ingredient	Persistence: Water/Soil	Persistence: Air	Bioaccumulation	Mobility
xylene	LOW	LOW	LOW	No Data Available
titanium dioxide	HIGH	No Data Available	LOW	HIGH
propylene glycol monomethyl ether acetate, alpha-isomer	HIGH	No Data Available	LOW	HIGH
methyl 1, 2, 2, 6, 6-pentamethyl-4-piperidyl sebacate	No Data Available	No Data Available	No Data Available	No Data Available

Section 13 - DISPOSAL CONSIDERATIONS

■ - Containers may still present a chemical hazard/ danger when empty.

- Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

- Where possible retain label warnings and MSDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction.

- DO NOT allow wash water from cleaning or process equipment to enter drains.

- It may be necessary to collect all wash water for treatment before disposal.

- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.

- Where in doubt contact the responsible authority.

- Recycle wherever possible.

- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

- Dispose of by: burial in a land-fill specifically licenced to accept chemical and / or pharmaceutical wastes or Incineration in a licenced apparatus (after admixture with suitable combustible material).

- Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.

Section 14 - TRANSPORTATION INFORMATION

Labels Required: FLAMMABLE LIQUID

HAZCHEM:

•3Y (ADG7)

ADG7:

Class or Division:	3	Subsidiary Risk:	None
UN No.:	1263	Packing Group:	III
Special Provision:	163 223 *	Limited Quantity:	5 L
Portable Tanks & Bulk Containers - Instruction:	T2	Portable Tanks & Bulk Containers - Special Provision:	TP1 TP29
Packagings & IBCs - Packing Instruction:	P001 IBC03 LP01	Packagings & IBCs - Special Packing Provision:	PP1

Name and Description: PAINT (including paint, lacquer, enamel, stain,

continued...

WATTYL POLY U400 MCR PART A

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Aug-2013

9317SP(cs)

CHEMWATCH 460365

Version No:10.1.1.1

CD 2013/2 Page 9 of 10

Section 14 - TRANSPORTATION INFORMATION

shellac, varnish, polish, liquid filler and liquid lacquer base) or
PAINT RELATED MATERIAL (including paint thinning or reducing
compound) (see 3.2.5 for relevant [AUST.] entries)

Air Transport IATA:

ICAO/IATA Class:	3	ICAO/IATA Subrisk:	None
UN/ID Number:	1263	Packing Group:	III
Special provisions:	A3		
Cargo Only			
Packing Instructions:	366	Maximum Qty/Pack:	220 L
Passenger and Cargo		Passenger and Cargo	
Packing Instructions:	355	Maximum Qty/Pack:	60 L
Passenger and Cargo		Passenger and Cargo	
Limited Quantity		Limited Quantity	
Packing Instructions:	Y344	Maximum Qty/Pack:	10 L

Shipping name:PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or
PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Maritime Transport IMDG:

IMDG Class:	3	IMDG Subrisk:	None
UN Number:	1263	Packing Group:	III
EMS Number:	F- E, S- E	Special provisions:	163 223 955
Limited Quantities:	5 L		

Shipping name:PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or
PAINT RELATED MATERIAL (including paint thinning or reducing compound)

Section 15 - REGULATORY INFORMATION

Indications of Danger:

Xn Harmful

POISONS SCHEDULE S5

REGULATIONS

Wattyl Poly U400 MCR Part A (CAS:) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6"

Regulations for ingredients

xylene (CAS: 1330-20-7) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia FAISD Handbook - First Aid Instructions, Warning Statements, and General Safety Precautions", "Australia Inventory of Chemical Substances (AICS)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix I", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6", "Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 7", "FisherTransport Information", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs"

TITANIUM DIOXIDE KRONOS 2063S (CAS: 13463-67-7,1317-70-0,1317-80-2,12188-41-9,1309-63-3,100292-32-8,101239-53-6,116788-85-3,12000-59-8,12701-76-7,12767-65-6,12789-63-8,1344-29-2,185323-71-1,185828-91-5,188357-76-8,188357-79-1,195740-11-5,221548-98-7,224963-00-2,246178-32-5,252962-41-7,37230-92-5,37230-94-7,37230-95-8,37230-96-9,39320-58-6,39360-64-0,39379-02-7,416845-43-7,494848-07-6,494848-23-6,494851-77-3,494851-98-8,55068-84-3,55068-85-4,552316-51-5,62338-64-1,767341-00-4,97929-50-5,98084-96-9) is found on the following regulatory lists;

"Australia Australian Pesticides and Veterinary Medicines Authority (APVM) Record of approved active constituents", "Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "FisherTransport Information", "International Agency for Research on Cancer (IARC) - Agents Reviewed by the IARC Monographs", "International Numbering System for Food Additives", "Sigma-AldrichTransport Information"

PGMA SOLVENT (CAS: 108-65-6,84540-57-8,142300-82-1) is found on the following regulatory lists;

"Australia Exposure Standards", "Australia Inventory of Chemical Substances (AICS)", "FisherTransport Information", "Sigma-AldrichTransport Information"

methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (CAS: 82919-37-7) is found on the following regulatory lists;

"Australia Inventory of Chemical Substances (AICS)"

continued...

WATTYL POLY U400 MCR PART A

Chemwatch Independent Material Safety Data Sheet

Issue Date: 30-Aug-2013

9317SP(cs)

CHEMWATCH 460365

Version No:10.1.1.1

CD 2013/2 Page 10 of 10

Section 16 - OTHER INFORMATION

Denmark Advisory list for selfclassification of dangerous substances

Substance	CAS	Suggested codes
propylene glycol monomethyl ether acetate, alpha- isomer	84540- 57- 8	Mut3; R68
methyl 1, 2, 2, 6, 6- pentamethyl- 4- piperidyl sebacate	82919- 37- 7	N; R50/53

INGREDIENTS WITH MULTIPLE CAS NUMBERS

Ingredient Name	CAS
titanium dioxide	13463- 67- 7, 1317- 70- 0, 1317- 80- 2, 12188- 41- 9, 1309- 63- 3, 100292- 32- 8, 101239- 53- 6, 116788- 85- 3, 12000- 59- 8, 12701- 76- 7, 12767- 65- 6, 12789- 63- 8, 1344- 29- 2, 185323- 71- 1, 185828- 91- 5, 188357- 76- 8, 188357- 79- 1, 195740- 11- 5, 221548- 98- 7, 224963- 00- 2, 246178- 32- 5, 252962- 41- 7, 37230- 92- 5, 37230- 94- 7, 37230- 95- 8, 37230- 96- 9, 39320- 58- 6, 39360- 64- 0, 39379- 02- 7, 416845- 43- 7, 494848- 07- 6, 494848- 23- 6, 494851- 77- 3, 494851- 98- 8, 55068- 84- 3, 55068- 85- 4, 552316- 51- 5, 62338- 64- 1, 767341- 00- 4, 97929- 50- 5, 98084- 96- 9
propylene glycol monomethyl ether acetate, alpha- isomer	108- 65- 6, 84540- 57- 8, 142300- 82- 1

■ Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

www.chemwatch.net/references.

■ The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

This document is copyright. Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH. TEL (+61 3) 9572 4700.

Issue Date: 30-Aug-2013

Print Date: 2-Sep-2013

This is the end of the MSDS.